CLAIM AMENDMENTS

Please amend the claims by amending claims 1 and 24 as indicated below, all without

prejudice, as indicated on the following listing of all the claims in the present application after

this Amendment:

Listing of Claims

1.(Presently Amended) A method for image sensing comprising the acts of:

producing, from a photo detector, a plurality of detected electronic signals responsive to

an optical image;

amplifying, with a column buffer amplifier, signals selected from the detected electronic

signals to produce a plurality of amplified signals;

sampling, with a correlated double sampler, signals selected from the amplified signals to

produce a plurality of sampled signals;

and

clamping, by a clamp circuit, at least one signal selected from and the sampled signals in

response to a detecting of at least one over-saturation condition;

whereby image inversion is at least partially abated.

2. (Original) The method of claim 1 wherein

the photo detector comprises a photo diode.

3. (Original) The method of claim 1 wherein

the photo detector comprises a photo gate.

4. (Original) The method of claim 1 wherein

the clamp circuit is implemented in a technology selected from a list consisting of N-well CMOS

process technology and of P-well CMOS process technology.

Claim 5-23: Cancelled.

EFS Filing

Attorney Docket No.: ZRAN.022US0

Application No.: 10/053,111

-2-

24.(Presently Amended) In an image sensor that correlates a first sample of a first signal during a first interval after reset of a photo detector and a second sample of the first signal during a later interval in the same sampling cycle as the first interval to produce a luminance signal, a method comprising for abating an error in the luminance signal due to excessively rapid slewing of the first signal during the first interval wherein the improvement comprises:

detecting that the first signal is slewing excessively rapidly during the first interval; and in response to said detecting, limiting the value of the first sample;

whereby the image sensor produces an output of improved accuracy by abating an error in the luminance signal due to said excessively rapid slewing.

- 25. (Original) The method of claim 24 wherein: the error is an image inversion due to over-saturation.
- 26. (Withdrawn) The method of claim 24 wherein: the detecting is responsive to the first signal reaching the bounds of a predetermined threshold.